


Chapter 1



```
.  
└── app.js  
└── routes  
    └── index.js
```

```
.  
└── app.js  
└── middleware  
|   └── errorhandlers.js  
|   └── log.js  
└── node_modules  
└── routes  
    └── index.js  
└── static  
    └── static.txt  
└── views
```

PacktChat

Index

PacktChat

Index

Cookie passed: {"test":"Test Cookie"}

PacktChat

Index

Cookie passed: {"test":"Test Cookie","IndexCookie":"This was set from Index"}

The screenshot shows the Chrome DevTools Network tab. On the left, there's a sidebar with options like Frames, Web SQL, IndexedDB, Local Storage, Session Storage, and Cookies. Under Cookies, 'localhost' is selected. A list of cookies is shown, with 'IndexCookie' having the value 'This was set from Index'. A context menu is open over this cookie, with the option 'Clear All from "localhost"' highlighted.

```
/  
[Error: `secret` option required for sessions]
```

PacktChat

Index

Cookie passed: {"test":"Test
Cookie","connect.sid":"s:19vJYsdMJ5DquOUqTDp0HhjD.ZWbMdo/J6oD6qqExln94TP5PglnU4wC+Olm76yCjaM","IndexCookie":"This was set
from Index"}

Session: {"cookie":{"originalMaxAge":null,"expires":null,"httpOnly":true,"path":"/"}}

PacktChat

Index

Cookie passed: {"test":"Test Cookie","IndexCookie":"This was set from Index"}

Signed Cookie passed: {"connect.sid":"0DMsXhobExvbCL3FFeYqRGWE"}

Session: {"cookie":{"originalMaxAge":null,"expires":null,"httpOnly":true,"path":"/"}}

| Name | Value |
|-------------|--|
| test | Test Cookie |
| connect.sid | s%3A0DMsXhobExvbCL3FFeYqRGWE.vhahB%2BEEv7gy2FgTXB2u1X8fbGoZw8roEUnxGxrWP7c |
| IndexCookie | This%20was%20set%20from%20Index |

PacktChat

Username

Password

[Login](#)

[Facebook](#)

[Google](#)

{ [Error: Forbidden] status: 403 }

PacktChat

Index

[Login](#)

PacktChat

Chat

Hello joshua [Logout](#)

[Login](#)

PacktChat

Wrong Username or Password

Username

Password

[Login](#)

[Facebook](#)

[Google](#)

Chapter 2

A screenshot of a browser's developer tools Network tab. The URL bar shows '<top frame> <page context>'. The status bar at the bottom says '(index):11'. A search bar contains the word 'ping'. Below it, a list of network requests is shown, with the first item being a POST request to 'ping' with the status 'Pending'.

- Josh Ping
- Josh has joined
 - Brian has joined
 - Josh has pinged!
 - Brian has pinged!

Josh Ping
Pings sent: 3

- Brian has joined
- Josh has joined
- Josh has pinged!
- Josh has pinged!
- Josh has pinged!

Josh Ping
Pings sent: 2

- Brian has joined
- Brian has pinged!
- Brian has pinged!

Josh Ping
• Brian has joined
• Brian has left :(

```

▼<li>
  "Brian"
    <button class="private_ping" data-socket="rrsfiJYsYYG4Y7ygrSV_">Ping Me</button>
  </li>

```

Josh

Default

Users

- Brian
- Kevin

Events

- Ping from Kevin sent directly to you!
- Ping from Kevin
- Ping from Brian
- Ping from Brian sent directly to you!
- Ping from Brian sent directly to you!

VIP

Users

- Kevin
- Brian

Events

- Ping from Brian sent directly to you!
- Ping from Brian sent directly to you!
- Ping from Brian
- Ping from Brian
- Ping from Kevin

▼ Watch Expressions

```

▼ io.nsps: Object
  ► /: Namespace
  ▼ /vip: Namespace
    ► _events: Object
    ► acks: Object
    ► adapter: Adapter
    ▼ connected: Object
      ► iNuUs-o17Moutm7jAAAA: Socket
    ► fns: Array[0]
    ids: 0
    name: "/vip"
    ► server: Server
    ► sockets: Array[1]

```

▼ Watch Expressions

```

▼ io.sockets.adapter: Adapter
  ► encoder: Encoder
  ► nsp: Namespace
  ▼ rooms: Object
    ► : Array[0]
    ► 3tEhBwhj9d34eJU2AAAA: Array[0]
    ► ikr3pDEdUpZiGSEXAAAB: Array[0]
  ▼ vip: Array[0]
    3tEhBwhj9d34eJU2AAAA: true
    ikr3pDEdUpZiGSEXAAAB: true
    length: 0
  ► sids: Object

```

```

Object {message: "Hey!"}                                (index):28
> |




▼ parsedCookie: Object
  connect.sid: "s:f0W06MohcxtjvlyQI1iZ6AYx.vMqCF23fVF3Tu5EwdgIVcyNb4TP9M8fkIaogE8uCVGw"
  sid: "f0W06MohcxtjvlyQI1iZ6AYx"


```

```
Object {message: "Hey!"}          chat:28  
Object {username: "joshua"}        chat:28
```

>

Chapter 3





PacktChat

https://developers.facebook.com/x/apps/729327833765884/settings/

Developers Apps Products Docs Tools Support Search in docs

PacktChat

Basic **Advanced** **Migrations**

| | |
|--|--|
| App ID 729327833765884 | App Secret ***** Show |
| Display Name PacktChat | Namespace packt_packtchat |
| App Domains | Contact Email Used for important communication about your app |
| Website | |
| Site URL http://localhost:3000 | |
| Mobile Site URL URL of your mobile site | |
| + Add Platform | |
| Delete App Discard Save Changes | |

PacktChat

<https://developers.facebook.com/x/apps/729327833765884/app-details/>

App Info

Fill out your App Details so that users can search for your app on Facebook. Once your app has high enough engagement and user ratings you can submit your app to be listed in our App Center.

Primary Language: English (US)

Tagline:

Short Description:

Long Description:

Publisher: Optional - Company that publishes this app

Category: Utilities

Explanation for Permissions:

Web Preview

Dashboard

Settings

Status & Review

App Details


Roles

Open Graph

Alerts

Localize

Payments



PacktChat

[Login](#)

Permissions error

Username

Password


[Login](#)

[f Facebook](#) [g+ Google](#)

PacktChat

Hello Joshua Johanan [Logout](#)



Chat



The screenshot shows the Google Developers Console interface. The top navigation bar includes links for 'Google Developers Console' and 'https://console.developers.google.com/project'. The main header says 'Google Developers Console'. On the left, there are navigation links for 'Projects', 'Billing', and 'Account settings'. A red 'CREATE PROJECT' button is located at the top right of the main content area. The main content displays a table of existing projects:

| PROJECT NAME | PROJECT ID | REQUESTS | ERRORS | CHARGES |
|--|----------------|----------|--------|---------|
| <input type="checkbox"/> API Project | | 0 | 0 | \$0.00 |
| <input type="checkbox"/> Geocode | | 0 | 0 | \$0.00 |
| <input type="checkbox"/> josh359 | josh359 | 95 | 9 | \$0.00 |
| <input type="checkbox"/> notepadappstest | notepadapptest | | | |

At the bottom of the table, there are buttons for 'Return to original console', 'Send feedback', and 'Privacy & Terms'.



Google Developers Console

OAuth

Create Client ID

Application type

Web application
Accessed by web browsers over a network.

Service account
Calls Google APIs on behalf of your application instead of an end-user. [Learn more](#)

Installed application
Runs on a desktop computer or handheld device (like Android or iPhone).

Authorized JavaScript origins

Cannot contain a wildcard (`http://*.example.com`) or a path (`http://example.com/subdir`).
`http://localhost:3000`

Authorized redirect URI

`http://localhost:3000/auth/google/callback`

[Create Client ID](#) [Cancel](#)

Google Developers Console

OAuth

Compute Engine and App Engine [Learn more](#)

| | |
|-------------------------------|--------------------------------|
| Client ID | apps.googleusercontent.com |
| Email address | @developer.gserviceaccount.com |
| Download JSON | |

Client ID for web application

| | |
|--|--|
| Client ID | .apps.googleusercontent.com |
| Email address | @developer.gserviceaccount.com |
| Client secret | Xnw |
| Redirect URLs | <code>http://localhost/auth/google/callback</code> |
| Javascript Origins | <code>http://localhost</code> |
| Edit settings Download JSON Delete | |

[Return to original console](#) [Send feedback](#) [Privacy & Terms](#)

PacktChat ▾

This app would like to:

 View your email address 

 View basic information about your account 

PacktChat and Google will use this information in accordance with their respective terms of service and privacy policies.

[Cancel](#)

[Accept](#)

Missing credentials

Username

username

Password

password

[Login](#)

 Facebook

 Google


Chapter 4


```
joshuas-mini:~ jjohanan$ brew install rabbitmq
=> Downloading http://www.rabbitmq.com/releases/rabbitmq-server/v3.2.3/rabbitmq
Already downloaded: /Library/Caches/Homebrew/rabbitmq-3.2.3.tar.gz
=> /usr/bin/unzip -qq -j /usr/local/Cellar/rabbitmq/3.2.3/plugins/rabbitmq_mana
=> Caveats
Management Plugin enabled by default at http://localhost:15672

Bash completion has been installed to:
/usr/local/etc/bash_completion.d


To have launchd start rabbitmq at login:
  ln -sfv /usr/local/opt/rabbitmq/*.plist ~/Library/LaunchAgents
Then to load rabbitmq now:
  launchctl load ~/Library/LaunchAgents/homebrew.mxcl.rabbitmq.plist
Or, if you don't want/need launchctl, you can just run:
  rabbitmq-server
=> Summary
🍺 /usr/local/Cellar/rabbitmq/3.2.3: 1038 files, 25M, built in 5 seconds
```

```
RabbitMQ 3.2.3. Copyright (C) 2007-2013 GoPivotal, Inc.
## ## Licensed under the MPL. See http://www.rabbitmq.com/
## ##
##### Logs: /usr/local/var/log/rabbitmq/rabbit@localhost.log
##### ## /usr/local/var/log/rabbitmq/rabbit@localhost-sasl.log
#####
Starting broker... completed with 10 plugins.
```





Message rates (chart: last minute) (?)



Global counts (?)

Connections: 1

Channels: 1

Exchanges: 9

Queues: 0

Consumers: 0

Bindings

This exchange



| To | Routing key | Arguments | |
|------------------|-------------|-----------|------------------------|
| first-queue-name | first-queue | | Unbind |

Bindings

From

Routing key

Arguments

(Default exchange binding)

my-first-exchange

first-queue

[Unbind](#)



This queue

Publish message

Routing key:

Delivery mode:

Headers: (?) = String

Properties: (?) =

Payload: OK


| Overview | | | | | Messages | | | Message rates | | |
|------------------|-----------|------------|--------|--------|----------|---------|-------|---------------|---------------|--------|
| Name | Exclusive | Parameters | Policy | Status | Ready | Unacked | Total | incoming | deliver / get | ack |
| first-queue-name | | | | Idle | | 9 | 0 | 9 | 0.00/s | 0.00/s |

```
{
  message: '/'
}
{
  message: '/favicon.ico'
}
{
  data: <Buffer 4f 4b>, contentType: undefined }
```


| Overview | | | | | Messages | | | Message rates | | |
|-----------|-----------|------------|--------|--------|----------|---------|-------|---------------|---------------|--------|
| Name | Exclusive | Parameters | Policy | Status | Ready | Unacked | Total | incoming | deliver / get | ack |
| debug.log | | | | Idle | | 7 | 0 | 7 | 0.00/s | 0.00/s |
| error.log | | | | Idle | | 1 | 0 | 1 | 0.00/s | 0.00/s |

```
Debug-Routing:debug.log{"url":"/css/style.css","ts":1397101112047}
Debug-Routing:debug.log{"url":"/","ts":1397103518502}
Debug-Routing:debug.log{"url":"/css/cosmo.min.css","ts":1397103518634}
Debug-Routing:debug.log{"url":"/css/style.css","ts":1397103518634}
Error-Routing:error.log{"error":"A contrived error","ts":1397101111988}
```

Request based



Socket.IO based



Chapter 5


```
joshuas-mini:finalChapters jjohanan$ brew install redis
=> Downloading https://downloads.sf.net/project/machomebrew/Bottles/redis-2.8.5
Already downloaded: /Library/Caches/Homebrew/redis-2.8.5.mavericks.bottle.tar.gz
=> Pouring redis-2.8.5.mavericks.bottle.tar.gz
=> Caveats
To have launchd start redis at login:
  ln -sfv /usr/local/opt/redis/*.plist ~/Library/LaunchAgents
Then to load redis now:
  launchctl load ~/Library/LaunchAgents/homebrew.mxcl.redis.plist
Or, if you don't want/need launchctl, you can just run:
  redis-server /usr/local/etc/redis.conf
=> Summary
🍺 /usr/local/Cellar/redis/2.8.5: 10 files, 1.2M
joshuas-mini:finalChapters jjohanan$
```

```
joshuas-mini:~ jjohanan$ redis-server
[1194] 13 Apr 17:23:49.473 # Warning: no config file specified, using the default config. In order to specify a config file use redis-server /path/to/redis.conf
[1194] 13 Apr 17:23:49.474 * Max number of open files set to 10032

                                     Redis 2.8.5 (00000000/0) 64 bit
                                     V
(   ,   |   )   Running in stand alone mode
|   ,   |   |   Port: 6379
|   ,   |   |   PID: 1194

http://redis.io

[1194] 13 Apr 17:23:49.475 # Server started, Redis version 2.8.5
[1194] 13 Apr 17:23:50.015 * DB loaded from disk: 0.539 seconds
[1194] 13 Apr 17:23:50.015 * The server is now ready to accept connections on port 6379
```



```
127.0.0.1:6379> KEYS *
1) "message:4:user"
2) "user:josh"
3) "user:3"
4) "message:2:user"
5) "message:5"
6) "user:2"
7) "user:brian"
8) "message:3:user"
9) "message:1"
10) "message:2"
```

```
[1351] 19 Apr 16:16:43.079 * 1 changes in 3600 seconds. Saving...
[1351] 19 Apr 16:16:43.079 * Background saving started by pid 1523
[1523] 19 Apr 16:16:43.080 * DB saved on disk
[1351] 19 Apr 16:16:43.180 * Background saving terminated with success
```

```
[1351] 19 Apr 15:16:42.209 # Server started, Redis version 2.8.5
[1351] 19 Apr 15:16:42.216 * DB loaded from disk: 0.007 seconds
[1351] 19 Apr 15:16:42.216 * The server is now ready to accept connections on po
rt 6379
```

Pub/Sub

- {"channel":"testpubsub","message":"Hey!"}
- {"channel":"testpubsub","message":"Another message"}

Chapter7

Please Select a Room

lobby

Brian

Hey what's up?



Josh

a few seconds ago

Hey what's up?

Josh

a few seconds ago

Not much

Brian

a few seconds ago



Josh

Send

Chapter 8

routes.js
✓ indexRouteTest

OK: 2 assertions (11ms)

Coverage summary =

Statements : 67.5% (54/80)
Branches : 28.57% (4/14)
Functions : 43.48% (10/23)
Lines : 67.5% (54/80)

Code coverage report for All files

Statements: 67.5% (54 / 80) Branches: 28.57% (4 / 14) Functions: 43.48% (10 / 23) Lines: 67.5% (54 / 80) Ignored: none

| File | Statements | Branches | Functions | Lines |
|-------------------------|------------|-----------|-----------|------------------|
| grunt_stuff/ | 100.00% | (2 / 2) | 100.00% | (0 / 0) |
| grunt_stuff/middleware/ | 100.00% | (20 / 20) | 100.00% | (4 / 4) |
| grunt_stuff/passport/ | 43.33% | (13 / 30) | 0.00% | (0 / 4) |
| grunt_stuff/routes/ | 67.86% | (19 / 28) | 0.00% | (0 / 6) |
| | | | 62.50% | (5 / 8) |
| | | | | 67.86% (19 / 28) |

Generated by [istanbul](#) at Sun Aug 10 2014 16:28:28 GMT-0400 (EDT)

```
20 | 1 function register(req, res){  
21 | 1   res.render('register', {title: 'Register', message: req.flash('error')});  
22 |};  
23 |  
24 | 1 function registerProcess(req, res){  
25 | 1   if (req.body.username && req.body.password)  
26 |{  
27 |   user.addUser(req.body.username, req.body.password, config.crypto.workFactor, function(err, profile){  
28 |     if (err) {  
29 |       req.flash('error', err);  
30 |       res.redirect(config.routes.register);  
31 |     }else{  
32 |       req.login(profile, function(err){  
33 |         res.redirect(config.routes.chat);  
34 |       });  
35 |     }  
36 |   };  
37 | }else{  
38 |   req.flash('error', 'Please fill out all the fields');  
39 |   res.redirect(config.routes.register);  
40 | }  
41 |};  
42 |
```

```
Linting js_src/src/chat.pre.js ...ERROR  
[L19:C4] W033: Missing semicolon.  
}
```

```
Running "uglify:dist" (uglify) task  
File static/js/ChatPage.4ab2340aa3394a13c6bb25699fb9ee31dad585c8.min.js created:  
15.06 kB → 9.91 kB  
File static/js/Frameworks.4ab2340aa3394a13c6bb25699fb9ee31dad585c8.min.js created:  
1.29 MB → 337.82 kB
```



Create User

Cancel

Your 1 User(s) have been created successfully.

This is the last time these User security credentials will be available for download.

You can manage and recreate these credentials any time.

▼ Hide User Security Credentials



test

Access Key ID: AKIAIMDBC6DNDMIHW2A
Secret Access Key: Bs1sdPQ+gbG9fhMFb/Tnye+qSQICje8NkiRLX/8Z

[Download Credentials](#)

[Close Window](#)

Chapter 9

```
ec2-50-19-156-37.compute-1.amazonaws.com | success > {  
  "changed": false,  
  "ping": "pong"  
}
```

```
└── ansible  
    └── roles  
        └── redis  
            └── tasks  
                └── main.yml
```

```
TASK: [redis | Install Redis] ****  
ok: [ec2-50-19-156-37.compute-1.amazonaws.com]
```


```
TASK: [redis | Bind to all Interfaces] ****  
ok: [ec2-50-19-156-37.compute-1.amazonaws.com]
```

```

└── rabbitmq
    ├── files
    │   └── rabbitmq.config
    └── tasks
        └── main.yml

```

SERVERID | 54.88.29.185



Chapter 10

Elements Network Sources Timeline Profiles Resources Audits Console

Events
Frames
Memory

| Name Path | Method | Status Text | Type | Initiator | Size Content | Time Latency | Timeline |
|--------------|--------|----------------|-----------|-----------|-----------------|-----------------|---|
| localhost | GET | 200 OK | text/html | Other | 197 B 11 B | 5 ms 4 ms | <div style="width: 100%;"><div style="width: 100%; background-color: #4CAF50; height: 10px;"></div></div> |

| Name Path | Method | Status Text | Type | Initiator | Size Content | Time Latency | Timeline |
|--------------|--------|--------------------|-----------|-----------|-----------------|-----------------|---|
| localhost | GET | 500 Internal Se | text/html | Other | 243 B 11 B | 14 ms 14 ms | <div style="width: 100%;"><div style="width: 100%; background-color: red; height: 10px;"></div></div> |

▼ Response Headers view source

Connection: keep-alive
Content-Length: 11
Content-Type: text/html; charset=utf-8
Date: Mon, 07 Jul 2014 03:00:34 GMT
ETag: W/"b-222957957"
Important-Header: test-value
X-Powered-By: Express

| | | | | | | |
|-----------|------|-----------|-----------|-------|--------------|--------------|
| localhost | POST | 200 OK | text/html | Other | 168 B 6 B | 3 ms 2 ms |
|-----------|------|-----------|-----------|-------|--------------|--------------|

▼ localhost:3000
 (index)
 debug.js

debug.js x

```
1 (function(){
2   var body = document.body;
3   (function(){
4     var div = document.createElement('div');
5     body.appendChild(div);
6   })();
7
8 })();
9
```

▶ ⌂ ⌂ ⌂ ⌂ ⌂

▼ Scope Variables

▼ Local

- div: div
- this: Window

▼ Closure

- body: body

► Global

```
webkit-devtools-agent: Spawning websocket service process...
webkit-devtools-agent: A proxy got connected.
webkit-devtools-agent: Waiting for commands...
webkit-devtools-agent: Websockets service started on 0.0.0.0:9999
```

| Self ▾ | Total | Aver... | Calls | Function | |
|--------|--------|---------|-------|-------------|--|
| 64.85% | 64.85% | 64.85% | 0 | (program) | |
| 34.98% | 34.98% | 34.98% | 0 | ► CPUWaster | /Users/ijohanan/django/finalChapters/debug/requests/app.js:7 |

| Constructor | Di... | Objects Count | Shallow Size | Retained Size ▾ |
|-------------|-------|---------------|--------------|-------------------------|
| ► Object | 2 | 529 | 1% | 16 248 0% 5 835 520 77% |



| | | | | | | |
|---------------------------|-------|---|--------|---------|-----|----------|
| ▼(closure) | 3 031 | 3 | +3 028 | 218 232 | 216 | +218 016 |
| ▼function() @98237 | * | | | 72 | | |
| ► express :: function cre | | | | | | |
| ► server :: Server @62621 | | | | | | |
| ► shared :: (shared func | | | | | | |
| ► 64 :: function() @10392 | | | | | | |
| ► __proto__ :: function E | | | | | | |

Object's retaining tree

Object

▼ [1386] in Array @98461

 ▼request in @62623

 ►_events in Server @62621

| Comparison ▼ Class filter | | | | Snapshot 1 ▼ | | |
|---------------------------|---------|------------|---------|--------------|------------|------------|
| Constructor | # New ▼ | # Delet... | # Delta | Alloc. Size | Freed Size | Size Delta |
| ► (array) | 62 282 | 544 | +61 738 | 2 451 860 | 66 988 | +2 384 872 |
| ► (system) | 34 466 | 1 800 | +32 666 | 326 584 | 30 460 | +296 124 |
| ► (closure) | 32 226 | 926 | +31 300 | 1 160 136 | 33 336 | +1 126 800 |
| ► Object | 30 187 | 76 | +30 111 | 485 832 | 2 240 | +483 592 |
| ► HTMLDi... | 30 001 | 0 | +30 001 | 600 016 | 0 | +600 016 |
| ► Detache... | 30 000 | 0 | +30 000 | 0 | 0 | 0 |